

RS ATM

RS ATM has been designed to transport different types of ATM cassettes in the same box. It has unlimited configuration options and can be adapted to any cash-in-transit (CIT) process.



- Compatible with Wincor Nixdorf, Diebold Opteva and NCR
- Compatible with 3SI Scorpion staining system
- Top cassette loading
- Robust
- Reliable

RS ATM

RS ATM has been designed to protect against attacks during ATM replenishment process. RS ATM fits one ATM cassette fitted with OCP or 3SI in-cassette staining system.

SPECIFICATIONS

	Capacity (cassettes)	Measures (in mm)	Weight (unloaded)	Battery life
RS ATM	1	W 399 x L 402 x H 640	16 kg.	3000 operation hours

SECURITY FEATURES

- Tamper proof = no unauthorized entry possible
- Radio-controlled opening at ATM
- Fully-encrypted communication protocol
- Fully programmable device with user-defined modes – total control of tour management
- User-defined timers for pavement, opening, vehicle transportation, etc.
- Additional levels of security for cross-pavement protection: electronic link, remote activation
- Time-restricted access (opening delays, opening time slots)
- Event logging and reporting (black box, real-time clock)
- Audible alarm and visual deterrent (smoke)
- Tamper evident seal can be retro fitted

DESIGNED FOR EASE OF USE

- Wireless access control, simple to use and secure
- Self powered
- Top or front cassette loading
- Robust casing and intelligent software, built for tough environments
- IP 65 (water tight)
- Large wheels and grab handle for uneven surfaces
- 1 guard can operate 2x RS ATM at once
- Secure in-vehicle storage using RS RACK

CASSETTE MANAGEMENT SYSTEM (OPTIONAL)

- For ATM cassettes with or without ink staining
- Same Process as with safe bags
- Inventory control
- Track & trace

